

## LOXAHATCHEE RIVER DISTRICT

2500 JUPITER PARK DRIVE, JUPITER, FLORIDA 33458

TEL: (561) 747-5700

FAX: (561) 747-9929

D. Albrey Arrington, Ph.D. EXECUTIVE DIRECTOR

loxahatcheeriver.org

# GRAVITY SEWER SERVICE INSTALLATION, MAINTENANCE, & SUSPENSION OF SERVICE INSPECTION PROCEDURES

**Engineering Department Contact Information Phone Number: 561-747-5700 extension 3** 

**Email:** <a href="mailto:engineering@lrecd.org">engineering@lrecd.org</a>

### **Suspension of Service / Cut and Cap Requests**

1. Please contact the District's Engineering Department to schedule a cut and cap inspection to suspend service during re-development of a property. A District Inspector must be on-site to the witness the cut and cap in order to suspend service.

### **Gravity Sewer Service Connection / Installation**

- 1. Please refer to the District's Engineering Plan Review Checklist. Approved plans must be in place prior to connection / installation.
- 2. Please contact the District's Engineering Department to schedule mandatory pre-construction meeting a minimum of 48 hours in advance prior to construction start.
- 3. All gravity sewer systems must be constructed in compliance with the District's Manual of Minimum Construction Standards and Technical Specifications posted on the District's website: <a href="http://www.lrecd.org/">http://www.lrecd.org/</a>

#### **Gravity Sewer System Maintenance**

- 1. The District maintains the gravity sewer mains and services within the public R/W and easements, except for the variations noted in Section 30.06 (c) of the District's Manual of Minimum Construction Standards and Technical Specifications . The Property Owner maintains the gravity service from the public R/W / easement to the residence / structure.
- 2. Each regional lift station that receives gravity flow is equipped with both visual and audible alarms. In the event of an alarm, please contact the District's emergency number 561-575-5708. The District has staff available 24 hours a day, 7 days a week.
- 3. The following items should <u>not</u> be introduced into the sanitary sewer system:
  - a. Glass
  - b. Metal
  - c. Cloth (sock, rags, etc.)
  - d. Plastic Objects (toys, utensils
  - e. Diapers, Diaper Wipes, Sanitary Napkins or Tampons

Gordon M. Boggie
CHAIRMAN

Kevin L. Baker BOARD MEMBER Stephen B. Rockoff
BOARD MEMBER

**Dr. Matt H. Rostock**BOARD MEMBER

- f. Fats, Oils and Grease (FOG)
- g. Bones and other grease-laden proeducts
- h. Dental Floss and Picks
- i. String, any kind
- j. Q-Tips
- k. Explosives
- l. Flammable Material
- m. Lubricating Oils and/or Greasen. Strong Chemicals
- o. Gasoline Paints
- 4. Access: District maintained clean-outs are installed 2" above sod grade for access. Please do not bury, cover or obstruct access.
- 5. Response During Emergency Conditions: When the District has declared Emergency Conditions (EMCON) based on District procedures, the District will maintain the regional lift stations until commercial power is restored.